

100 N. Gordon St. Elk Grove Village, IL 60007-1193 Phone (847) 956-1600 Fax (847) 956-0595 E-mail: info@halco-products.com Website: www.halco-products.com

4/27/2021

Air Shower and Air Shower Tunnels







Air Showers offer an effective way to reduce contaminants carried by individuals entering or leaving a controlled area. The Air Shower can solve many of your decontamination problems.

Construction Options

- **♦** Cold Rolled Steel Painted or Unpainted
- ♦ Stainless Steel 304, 316, or 321

Typical Components

1. Motor/Blower assembly. 2. Power control box. 3. Emergency release button Reset—Alarm.

4. HEPA filter 99.97% effective on .3-micron particles. 5. Adjustable nozzles.

6. LED light fixture 7. Automatic activated floor switch. 8. Anodized aluminum doors with plexiglass.

9. Microprocessor control panel—On/Off lights. 10. Access panels for easy maintenance.

11. Electric interlocking chamber. 12. Single connection junction box.

OPTIONAL EQUIPMENT/MODELS

Magnahelic Gauge HEPA. Safety Plate Glass Doors. Magnahelic Gauge Prefilter.

Photohelic Gauges with Alarms. Roll-up Doors Auto Bi-part Doors. Aluminum Grated Floor with Clean Out Pan. Sprinkler Head. Laminar Ceiling Blower. **Ionization Bars** Proximity Sensor.

TEFC or Special Frame Motors.

SPECIAL HALCO AIR SHOWER FEATURES

SOLID STATE ELECTRICAL PLC SYSTEM CONTROL PANEL INCLUDES:

Light Switch, audible alarm and alarm reset.

4 Line 64-character alpha/numeric LCD display which monitors system function during normal operation and displays menu functions for service and system changes.

4.3" graphic HMI LCD display for system operation.

- 4 Number code to turn control on and off
- 4 Number code to get into systems setup
- PLC programming capabilities:
- Program time of day
- Program day of the week
- Program cycle time
- Program delays unlock time
- Designate entry and exit doors

Products for the HVAC and Clean Room Industry Visit our WEBSITE at www.halco-products.com

S:\Data\Word\HALCO\Air Showers and PARTS\CHECKLISTS-SPECIFICATIONS- DESIGN\AIR SHOWERS and TUNNELS OPTIONS and DETAILS.docx



100 N. Gordon St. Elk Grove Village, IL 60007-1193 Phone (847) 956-1600 Fax (847) 956-0595 E-mail: info@halco-products.com Website: www.halco-products.com

- Program new 4-digit code enter system
- Program time lock feature
- Initiate security locking feature with 4-digit code Initiate single direction access feature
- Interlocking doors (standard), which release automatically with power failure.
- LED lighting (standard) is contained in the ceiling for less turbulence. HEPA Ceiling (optional) for constant laminar flow for added protection.
- Ionized Grid (optional) to eliminate static electricity when required.
- Halco warrants their units for (1) year from date of delivery for defects in workmanship.
- In case of power failure, locks automatically release for exiting. An emergency stop button on each Air Shower sounds an alarm and releases locks for exiting.
- PLC diagnostic capabilities:
- Air shower disabling feature
- Blower operations check
- Door switch operations check
- Door lock operations check
- Presence sensor/mat switch check
- Record blower run hours
- Record air shower cycles